



DX660F Flexo CTP Plate Making Machine



- The marble base can control the expand with heat and contract with cold effectively, thus ensure the output resolution under any environmental temperature.
- Reliable laser unit, easy to maintain, sharp printing dots with good quality, high resolution, dot recovery 1%-99% under 300lpi
- The independent dust control system keep laser units clean and the reliable output quality.
- The external drum structure keeps the circumferential direction of the plate same during the plate making process and printing process, which ensure the stable dots shape, to achieve the best combination results of plate making and printing.
- CTP system provides optional automatically punch system to realize accurate overprinting.



- Continuous plate-loading is available with double plate bed. Front unloading & back unloading is optional and the on-line processing operation can be achieved with automatic bridge.
- The open control system makes laser power adjustable, output speed adjustable, plate parameter adjustable and convenient operation

Technical Parameters

Model	DX660F-16	DX660F-32	DX660F-48
Laser system	16	32	48
Productivity	1.4 m ² /h	2.8 m ² /h	4.2 m ² /h
Min.plate size	100mm*100mm		
Max.plate size	660mm*810mm		
Plate thickness	0.15-3.94mm		
Output media	Digital flexo letterpress plates; Digital flexo water-washable plates; Digital solvent flexo plates		
Application	Label printing、 Trade mark、 Packaging		
Resolution	4000dpi		
Interface	Gigabit Ethernet		