



Libao Series TYMK-750W 930W 1100W High Configuration Hot Foil Stamping Machine



- High strength due to one piece casting by using top-ranking material for machine body.
- Single plate electromagnetic clutch is sensitive and reliable.
- Computer controlled is stable.
- Operation position is reasonably arranged, moving- -bed can be opened to its optimum.
- Skipping is accurate, so as to save foils.
- With three functions of continuous creasing and cutting, opening dwell operation and closing dwell operation and a large dwell adjusting range.
- Safety system is reliable.
- Central lubrication system guarantees fine lubrication and reduce friction.



主要技术参数 Main Specification:

型号 Model	最大有效压切面积 Max. Platen area available	最大烫印面积 Max. Stamping area available	跳步指定范围 Range of skip order	工作压力 Working pressure	送箔长度 Foil-delivered length
TYMK-750W	750 × 520mm	660 × 480mm	微机内部处理 Built-in Processing With Computer	150T	520mm
TYMK-930W	930 × 670mm	930 × 640mm	微机内部处理 Built-in Processing With Computer	170T	640mm
TYMK-1100W	1100 × 800mm	1100 × 800mm	微机内部处理 Built-in Processing With Computer	220T	800mm

型号 Model	送箔组数 Foil-delivered group	工作速度 Working speed	主机功率 Main motor power	总功率 Total power	机器重量 Net Weight	外形尺寸(长 × 宽 × 高) Deminsion (L × W × H)
TYMK-750W	2组 (groups)	1600 (strokes/h)	2.2kw-6H	7 (kw)	2200 (kg)	1900 × 1450 × 1950mm
TYMK-930W	3组 (groups)	1320 (strokes/h)	7.5kw-4H	16(kw)	3800 (kg)	1800 × 1900 × 2150mm
TYMK-1100W	3组 (groups)	1200 (strokes/h)	5.5kw-6H	18(kw)	4900 (kg)	2150 × 2150 × 2300mm